

Features

Classic square shape has a minimalist look and a modern feel to reflect your personality.

The sturdy and durable surface will give you many years of dependable service.

This door release button features a quality push button. It is a reset push button with a flexible feel. It can be used for controlling the door release.

It can be used for any access control application and is commonly used in offices, banks, gas stations, department stores and many more.

Installation steps



1

Step 1:
Remove the external screws of the switch using a screwdriver.



2

Step 2:
After determining the installation position of the switch, fix the bottom mounting piece with screws.

(Screws can be fixed in the red circle)



3

Step 3:
Plug the connected good line, and then close each part of the switch, screw the installation is completed.

Specifications

EB-1405	Without LED	Mechanical Life	5000000 tested
Dimensions	80Lx30Wx24H(mm)	Suitable for Door	Hollow Door
Standard Structure	Stainless steel Panel, Steel Button	Operating temp	-10 C ~ 55°C (14°F-131°F)
Current Rating	3A,36VDC Max	Operating Humidity	0-95% (non- condensing)
Material	Zinc Alloy	Weight	0.133kg
Voltage	12VDC	Standard Packing	100pcs
Current	3A	Faceplate	Alloy panels high-temperature paint
Output Contact	NO\COM		

Dimensions



Wiring Diagram

